

| Product                       | Form  | Application   | Benefits   | D5<br>sed<br>igraph | D98<br>sedi<br>graph            | Brig<br>htn<br>ess<br>[GE<br>B] |
|-------------------------------|---|---|--|---------------------|---------------------------------|---------------------------------|
| <b>NICRON®<br/>302</b>        | Natural white powder, bags  | Sealants and Caulks, Pressure Sensitive and Structural Adhesives  | High loading low viscosity, high brightness  | 13                  | ca. 30 (Hegman 3)               | Y82                             |
| <b>SILVERLINE®<br/>E® 303</b> | Natural white powder, bags  | Pastes & Mastics, cementitious and self-leveling Compounds, fine  | Finer top-size for smooth Finishes and application properties  | 6,1                 | ca. 40                          | 78                              |
| <b>VERTAL®<br/>92</b>         | Natural white powder, talc/carbonate mineral pigment, bags                        | Auto Rep Grouts, Car Putties Autofill                             | Highly lamellar talc, macrocrystalline 200 Mesh, good sanding for abrasive paper use   | 17,5                | ca. 45                          | Y72                             |
| <b>VERTAL®<br/>97</b>         | Natural white powder, talc/carbonate mineral pigment, bags                        | Pastes & Mastics, cementitious and self-leveling Compounds        | Highly lamellar talc, macrocrystalline 200 Mesh, good sanding for abrasive paper use   | 15                  | 50                              | Y72                             |
| <b>SILVERLINE®<br/>E® 002</b> | Natural white powder, bags  | Pastes & Mastics, cementitious and self-leveling Compounds        | High loading low viscosity   | 8,4                 | 55                              | 75                              |
| <b>VERTAL®<br/>TC-100</b>     | Natural white powder, talc/carbonate mineral pigment, bags                        | Pastes & Mastics, cementitious and self-leveling Compounds        | Improves resistance to cracking, smoothing and sandability, macrocrystalline 200 Mesh  | 16,4                | 325 Mesh (44 µm) %passing 88    | off white                       |
| <b>VERTAL®<br/>AF</b>         | Natural white powder, UL Environment labeled for sustainability, only BB 2000 lbs | Construction, Bitumen Roofing, Flooring, Adhesives, Sound Damping | Talc with high carbonate (Mg) content, improved dimensional stability, cross-flow mechanical performance, and flexural stiffness | 23                  | 325 Mesh (44 µm) %passing 60-85 | off white                       |